

DRIVER:	Starting setup carpet (V2)	TRACK:		TRANSMITTER:		BATTERY:		TIRES:	
DATE:		SURFACE:	ASPHALT ☐ CARPET ☒	RECEIVER:		MOTOR:		ADDITIVE:	
OUTSIDE TEMPERATURE°C:		LAYOUT:	TECHNICAL ☐ MIXED ☐ FAST ☐	SERVO:		PINION TYPE & T:		WARMER C°:	
TRACK TEMPERATURE°C:		TRACTION:	LOW ☐ MEDIUM ☐ HIGH ☐	STEERING EXPO:		SPUR TYPE & T:		WARMER TIME:	
VER. 3101-1		RACE:		STEERING SPEED:				SIDEWALL GLUE:	
		RESULT:							

☒ CLIP ☐ O-RING FF (mm) 0 FR (mm) 0,5 RIDE HEIGHT (mm) 5 UPTAVEL LIMIT (mm) 14 FF 2 FR 2	ACTIVE ☐ FIXED ☒ (mm) 3 (mm) 0,5 (mm) 5 CAMBER° 1,5 TOE OUT° 125 DOWNSTOP(mm) 23,6 INSIDE ☒ OUTSIDE ☐ CASTER° 4 OUT (3mm) ☐ 2,5mm ☒ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm ☐ IN (0mm)	☒ F/R ☐ (mm) 15 VERTICAL ☒ (ONLY USE WITH INNER POSITION ON THE LOWER WISHBONE) HORIZONTAL ☐ BYPASS ☐ PISTON OPT. ☐ SPRING 4,5 OIL# 400 1,5 (mm) 1,1 1,2 1,3 -0,5 0 0,5 HORIZONTAL ☐ BYPASS ☐ PISTON OPT. ☐ SPRING 4,25 OIL# 400 (mm) 1,1 1,2 1,3 -0,5 0 0,5	CAMBER° (mm) 1,5 TOE IN° 3 DOWNSTOP(mm) 22,4 OUT (3mm) ☐ 2,5mm ☒ 2,0mm ☐ 1,5mm ☐ 1,0mm ☐ 0,5mm IN (0mm) ☐	(mm) 4 (mm) 1 INSIDE ☒ OUTSIDE ☐ RIDE HEIGHT (mm) 5,2 UPTRAVEL LIMIT (mm) 14 RF 15 RR 15 UPPERARM POSITION
--	---	--	---	--

☐ CUT ☐ CUT TYPE (mm) 2	☒ UP (KIT) (MSE#MA2051) LOW ☐	0 WEAK HARD 21023 WEAK HARD 0 ☒ UP (KIT) ☐ LOW (MSE#MA2051)	☒ ☐ ☒ TYPE (mm) 2,25
ROD POS. ☒ STD ☐ OPT STEERING° OUTSIDE 15 INSIDE ~23	SCREW POS. (mm) ~17	CHASSIS TYPE Kit CAR WEIGHT (g) 1280 WEIGHT BALANCE F%/R% 50/50 MOTORMOUNT SCREW WEIGHT UNDER BATTERY (g) 1 2 3 4 g (UNDER PINION) g g g (UNDER ESC) g (UNDER RECEIVER) 50% / 50% = CENTER (± 0.5% each step) WEIGHT (g) F R WEIGHT ON A2440 (g) WIDE ☒ NARROW ☐ (mm) 29	OIL# 7K OIL (g) 1,5 (A2248D alu) ☐ SHIM (mm) 1 BODY SHELL & WING TYPE SIDE STIFFENER ☒ Speciale (mm) ~75 DISTANCE TO CHASSIS (mm) 65 (mm) 93 WINGLET ☒
INFO			