

DRIVER	Kit Std. Setup EU Asphalt	
DATE		
TRACK	Carpet <input type="radio"/> Asphalt <input checked="" type="radio"/>	
TRACTION	<input type="radio"/> LOW <input checked="" type="radio"/> MEDIUM <input type="radio"/> HIGH	
LAYOUT	<input type="radio"/> SLOW <input checked="" type="radio"/> MIXED <input type="radio"/> FAST	
TEMP °C	AIR	TRACK
ELECTRONICS		
ESC	ESC SET	MOTOR
SERVO	RECEIVER	BATTERY
TIRES		
BRAND	Ride	
TYPE	ETS	
ADDITIVE	MR33 V3	
WARMER °C	FRONT 60°	REAR 60°
TIME(min)	FRONT 15	REAR 15
SHOCK ABSORBERS		
PISTON	FRONT Std.	REAR Std.
SHOCK CASE	Std.	
OIL	350 350	
SPRING	6.0P 6.75	
LENGTH	9.5	9.5
ANTI ROLL BAR FRONT/REAR		
FRONT	1.1	REAR 1.2
DIFF	<input checked="" type="radio"/>	SPOOL <input type="radio"/>
OIL CST	1.000K	
GEAR RATIO (T)Spur/(T)Pinion*1,9=Ratio		
PINION		SPUR
AERODYNAMIC SETTINGS		
BODY TYPE	Blitz MK9	
WING TYPE	Std.	
WING POS	(mm)	Std.
BODY POSITION (see picture below)	(mm) \leftrightarrow horizontal	55
FRONT BODY HEIGHT & POSITION	REAR BODY POST A2407C <input checked="" type="radio"/>	REAR BODY POST A2416B <input type="radio"/>
(mm) vertical \updownarrow	59	(mm) 57

STEERING LIMITER

A2304 (5mm)

A2305 (5.5mm)

A2306 (6mm)

STEERING ANGLE IN°

STEERING ANGLE OUT°

A2427 USED

YES NO

A2427 SHIM(mm)

UPPER ARM POS. FR(mm)

FF(mm)

LOWER ARM POS. FR(mm)

FF(mm)

SHOCK POS (mm)

STEERING ROD POS (mm)

SHIM UPRIGHT L (mm)

UPPERARM POS. (CASTER)

REAR/5° FRONT/4°

SHIM UPRIGHT T(mm)

CAMBER/°

TOE OUT/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

A2529 POSITION

INSIDE

OUTSIDE

A2530 POSITION

INSIDE

OUTSIDE

ACKERMANN SHIM (mm)

SHIM S HORN (mm)

LENGTH S HORN (mm)

REAR TOE ROD POS

FRONT REAR

UPPERARM POS. (CASTER)

FRONT/-4° REAR/-3°

TYPE SERVO HORN

SHIM UPRIGHT T (mm)

CAMBER/°

TOE IN/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

UPPER ARM POS. RF(mm)

RR(mm)

LOWER ARM POS. RF(mm)

RR(mm)

SHOCK POS (mm)

TOE ROD POS (mm)

SHIM UPRIGHT L (mm)

UPPERARM POS. (CASTER)

FRONT/-4° REAR/-3°

A2219 **A2224**

CAMBER/°

TOE IN/°

OFFSET (mm)

RIDE HEIGHT(mm)

DOWNSTOP(mm)

A2430(40g)

A2432(85g)

BATTERY POSITION

WEIGHT POSITIONS (g)

A B C D E

FRONT/REAR WEIGHT DISTRIBUTION HOLE#

A2419

A2419 SCREW

MM SCREW

BELT TENSION

1pc. UPPERDECK TYPE

OVERALL WEIGHT(g)

SHOCK TOWER

A2524F **A2542**

A2524R **A2543**

A2158

UPPERDECK SCREW

UPPERDECK BEARING

2pc. UPPERDECK

FRONT SCREWS

REAR SCREWS

FRONT (BULKHEAD)

FRONT (2pc.UPPERDECK)

REAR (UPPERDECK)

REMARKS

Find more setup's under www.mugenseiki.co.jp